Company name: GS Yuasa International Ltd.

Page 1 / 19

Date of issuing: 2018/2/7 Date of revision: 2020/4/20

Latest confirmation date: 2020/4/20

PRODUCT INFORMATION SHEET

Lead-acid battery is not a target product for SDS (safety data sheet).

This sheet is intended to be issued in order to provide "reference information" to ensure the safe handling of the product.

1. Chemical Product and Company Identification

Product name : Small-sized valve regulated lead-acid battery

NP, PE, PX, PXL (non-Flame retardant).

(*Except for products marked "FLAME RETARDANT".)

Information on company

Company name : GS Yuasa International Ltd.

Relevant dept. : Industrial Battery Production Division

Industrial Batteries & Power Sources Business Unit

Address : 1,Inobanba-cho,Nishinosho,Kisshoin,Minami-ku,Kyoto,601-8520,Japan

Phone number :81-75-312-0702 **Fax number** :81-75-312-0379

2. Hazards Identification

GHS classification

Physical and chemical hazards : Not applicable
Health hazards : Not applicable
Environmental hazards : Not applicable

GHS label elements:

Pictogram : None
Signal words : None
Hazard statements : None
Precautionary statement : None

Other risks/hazards : No information

3. Composition/Information on Ingredients

Information on composition and ingredients:

NO.	Chemical name or common name	Component part	Content rate (mass ratio)	Chemical formula	CAS no.
	Lead, Lead compounds (Lead dioxide, Lead sulphate etc.)	Terminal, electrode plate	60-75%	Pb	7439-92-1
1				PbO ₂	1309-60-0
				PbSO ₄	7446-14-2
2	Barium compound	electrode plate	0.3% or below	Ва	7440-39-3
2				BaSO ₄	7727-43-7
3	Dilute sulfuric acid (27~50%)	Electrolyte	12-25%	H ₂ SO ₄	7664-93-9
4	ABS resin	Battery	E 450/		0000 50 0
		container, lid	5-15%	-	9003-56-9

Company name: GS Yuasa International Ltd.

Page 2 / 19

Date of issuing: 2018/2/7 Date of revision: 2020/4/20

Latest confirmation date: 2020/4/20

5	Glass	Separator	1-3%	-	-
6	Brass etc.	Other metal parts	1% or below	-	-
7	Polypropylene, Epoxy resin, rubber etc.	Other resin parts	5% or below	-	9003-07-0(PP)

-		
4.	First-aid	l Measures

If inhaled : (Lead, lead dioxide, lead sulfate, dilute sulfuric acid)

Remove person to fresh air, keep comfortable for

breathing.

Get medical advice/attention.

If on skin : (Lead, lead dioxide, lead sulfate)

Wash skin with plenty of water and soap.

If skin irritation occurs, get medical advice/attention.

(dilute sulfuric acid)

Take off or remove immediately all contaminated clothing.

Rinse skin with water or shower.

If skin irritation or chemical injury occurs, get medical

advice/attention.

If in eyes : (Lead, lead dioxide, lead sulfate, dilute sulfuric acid)

Open the eyelids with your fingers, rinse thoroughly with

water for at least 15 minutes.

Remove contact lenses, if present and easy to do.

Continue rinsing.

Get medical attention/advice.

If swallowed : (Lead, lead dioxide, lead sulfate)

Rinse mouth.

Get medical advice/attention.

(dilute sulfuric acid)

Rinse mouth.

Give plenty of water.

Do not induce vomiting.

Get medical advice/attention.

Most important symptoms/effects,

acute and delayed

: (Lead, lead dioxide, lead sulfate)

Stomach cramps, lethargy, headache, nausea, vomiting, weakness, wheezing, pallor, hemoglobinuria, collapse.

(dilute sulfuric acid)

Corrosive, burning sensation, sore throat, cough, breathlessness, shortness of breath, redness, pain,

blisters, severe skin burns, severe burns, abdominal pain,

shock or collapse.

Protection for first-aiders : Rescuers wear protective equipment such as rubber gloves

and tight-fitting safety goggles.

Special note to physician : (Dilute sulfuric acid)

Symptoms of lung edema often do not show until a few

Product name: Small-sized valve regulated lead-acid battery(non-Flame retardant)

Company name: GS Yuasa International Ltd.

Page 3 / 19

Date of issuing: 2018/2/7 Date of revision: 2020/4/20

Latest confirmation date: 2020/4/20

hours have passed, and it might aggravate if it does not take a rest. Therefore, it is necessary to take a rest and

medical observation.

5. Fire Fighting Meas	sures	S
-----------------------	-------	---

: Extinguish the fire by extinguishers of dry chemical agent, Suitable extinguishing media

foam fire extinguish agent, and non-flammable gas.

Unsuitable extinguishing media

: No information.

Specific risk/hazard

: In case of fire, there is a possibility that irritative, corrosive or

toxic fumes or gases are generated.

There is a possibility of explosion of the product by heat.

Specific fire fighting method : Cut off the power in case of connection/energizing the

product into the device, if can be coped with safely. Move the product from the fire area if it is not dangerous. After extinguishing the fire, continue to cool the container

thoroughly with plenty of water.

Immediately move the movable product to safe place when

fire occurs in surrounding. If it is not movable, cool the

product with water spray.

Keep away the combustible materials to prevent spread fire

around.

Protection for fire-fighters : Extinguish fire from upwind.

Wear appropriate protective clothes for chemical

(self-contained breathing apparatus, protective glasses, etc.)

to fire fighting.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency measures : Wear appropriate protective equipment (gloves, protective

glasses, protective clothing and the like), when processing

the leakage.

Do not touch or walk through the leakage.

Do not breathe dust, mist and vapour.

Precautions for the environment : Be careful to not discharge the product into the rivers, sewer,

and soil.

Method for containment and clean-up : If dilute sulfuric acid is leaked, stopping the flow with sand

and earth, absorbing mat and the like, remove by absorbing with them. And then, neutralized with sodium bicarbonate or

slaked lime, and wash off with plenty of water.

Absorb by sprinkling misty water when the gas is generated.

Collected material should be disposed in compliance

with '13. Disposal Considerations'.

Prevention of secondary hazards : Immediately remove all ignition sources in the vicinity.

Prepare fire extinguishing equipment just in case it is ignited.

Company name: GS Yuasa International Ltd.

Page 4 / 19

Date of issuing: 2018/2/7 Date of revision: 2020/4/20

Latest confirmation date: 2020/4/20

7. Handling and Storage

Handling

Technical measures : Take measure described in '8: Exposure Controls and

Personal Protective Equipment', and wear appropriate

protective equipment.

Local exhaust/general ventilation : Work in a well-ventilated place and provide local exhaust or

general ventilation as necessary.

Cautions for Safety Handling : Do not use fire near the product.

Do not dismantle or modify the product.

Do not do short-circuit between the terminals.

Handling and charging of the product should be in well

ventilated place.

Prevent falling and overturning of container. Careful to not

give a shock.

Try to not damage the product.

Be careful that there is a possibility of spewing dilute sulfuric

acid from the vent plug of product when open.

Be careful not to spill the dilute sulfuric acid.

Do not eat, drink or smoke when using this product.

Storage

Technical measures : Provide a ventilation and lighting required for storing and

handling hazardous materials in the storage location.

Storage condition : Do not store near the fire.

Do not store in place where is exposed to high temperature,

high humidity, rain, direct sunlight.

Store in place where is no risk of fire, toxic gas, liquid droplets, generating or invasion of dust, and submerged.

8. Exposure Controls and Personal Protective Equipment

Controlled exposure level : Lead (electrode plate, terminal), lead dioxide(electrode

plate), lead sulfate(electrode plate) Lead and its compounds(as lead)

TLV = 0.05 mg/m^3

Permissible exposure level

Japan Society for Occupational

Health (2014)

: Lead(electrode plate, terminal), lead dioxide(electrode

plate), lead sulfate(electrode plate)

Lead and its compounds(as lead): TLV = 0.1 mg/m³

Dilute sulfuric acid(electrolyte)

Sulfuric acid: Maximum permissible exposure limit =

1mg/m³

ACGIH (2014) : Lead(electrode plate, terminal), lead dioxide(electrode

plate), lead sulfate(electrode plate)

LEAD AND INORGANIC COMPOUNDS, AS Pb

TLV-TWA = 0.05 mg/m³ Dilute sulfuric acid(electrolyte)

Sulfuric acid: TLV-TWA = 0.2mg/m³

Product name: Small-sized valve regulated lead-acid battery(non-Flame retardant)

Company name: GS Yuasa International Ltd.

Page 5 / 19

Date of issuing: 2018/2/7 Date of revision: 2020/4/20

Latest confirmation date: 2020/4/20

Engineering controls : Provide hand wash and eyes wash facilities and safety

shower near the handling place as necessary.

Personal protective equipment

Respiratory protection : Wear respiratory protective equipment (air respirator, dust

mask, gas mask (for acid gases)) as necessary.

Hand protection : Wear impermeable protective gloves (acid resistance).

Eye protection : Wear protective glasses, goggle type safety glasses and the

like.

Skin and body protection : Wear protective clothing, protective apron and the like as

necessary.

Hygiene measures : Do not eat, drink or smoke when handling.

Wash hands thoroughly after handling.

Protective equipment shall be inspected regularly according

to the protective equipment checklist.

9. Physical and Chemical properties

Describes the information about the components below.

	Lead	Lead dioxide	Lead sulfate	Dilute sulfuric acid
Appearances (physical state, form, color, etc.)	Silver white solid	Brown crystal or powder	White crystal	Colorless transparent liquid
Odor	No information.	No information.	No information.	Odorless (normal temperature)
Threshold of odor	No information.	No information.	No information.	No information.
рН	No information.	No information.	No information.	≦1
Melting point	327.4°C	888°C	1170°C	≦-40°C(s.g.1.30)
Boiling point, initial boiling point and boiling range	1,749°C	1,480°C	No information	114°C(s.g.1.30)
Flash point	Non flammable	Non flammable	Non flammable	Non flammable
Flammability(solid, gas)	Non flammable	Non flammable	Non flammable	Not applicable
Specific gravity(density)	11.35g/cm ³ (20°C)	9.53g/cm ³	6.2	Approx. 1.2∼1.4
Solubility	Water: Insoluble.	Water: Insoluble.	Water: Hardly soluble.	Miscible in water. Soluble in alcohol.
Partition coefficient (n-octanol/water)	No information.	No information	No information	No information
Auto-ignition temperature	Non flammable	Non flammable	Non flammable	Non flammable
Decomposition temperature	No information.	290°C	1000°C	No information
Viscosity	No information.	No information.	No information.	No information.
Other Information	No information.	No information.	No information.	No information.

Product name: Small-sized valve regulated lead-acid battery(non-Flame retardant)

Company name: GS Yuasa International Ltd.

Page 6 / 19

Date of issuing: 2018/2/7 Date of revision: 2020/4/20

Latest confirmation date: 2020/4/20

10. Stability and Reactivity

Stability : (lead)

When oxygen is present, it will be eroded by pure water and the weak organic acid. At normal temperature, it will be eroded by fluorine or chlorine.

(lead dioxide/ lead sulfate)

It is considered to be stable under normal handling and storage.

(dilute sulfuric acid)

At first, vapor is generated by heating, and generate sulfuric acid vapors if continue to heat.

Rapid contact with water might be generate a large amount of heat, and sometimes the acid is scattered.

Dilute sulfuric acid which is generated by diluting with water, generates hydrogen gas by the corrosion of various metals and may cause flash explosion by mixing with air.

There is hygroscopic.

Hazardous reactivity : (lead)

It does not occur hazardous reaction under normal condition.

(lead dioxide)

React violently with combustible materials and organic matter (sulfuric acid, hydrogen peroxide, phosphoric acid), and it may cause risk of fire.

(lead sulfate)

It may react with strong oxidizing agents.

(dilute sulfuric acid)

It may cause fire or explosion by many reactions. It is strong oxidant and reacts with combustible and reducing materials.

It is strong acid and reacts violently with bases and is corrosive to most common metals forming a

flammable/explosive gas(hydrogen).

React with water and organic materials violently and release heat.

Conditions to avoid : Heating, contact with ignition sources (open flame, spark,

etc.,)

Incompatible materials : (lead): Oxidizing agent.

(lead dioxide): Flammable materials, reducing materials.

(lead sulfate): Strong oxidizing agents.

(dilute sulfuric acid):

Combustible materials, reducing materials, strong oxidizing agents, strong bases.

Hazardous decomposition products : In case, there is a possibility that irritative or toxic gases or

fumes (sulfur trioxide, carbon monoxide, mist sulfate, sulfur

Product name: Small-sized valve regulated lead-acid battery(non-Flame retardant)

Company name: GS Yuasa International Ltd.

Page 7 / 19

Date of issuing: 2018/2/7 Date of revision: 2020/4/20

Latest confirmation date: 2020/4/20

dioxide, hydrogen sulfide) are generated.

11. Toxicological Information

Indicate the information for each of components of lead acid battery as below.

OLead (electrode plate, terminal)

Acute toxicity (Oral) : No data.
Acute toxicity (Dermal) : No data.

Acute toxicity (Inhalation: Gases) : Classification not applicable because it is a solid in the

definition of GHS.

Acute toxicity (Inhalation: Vapours) : No data.

Acute toxicity : No data.

(Inhalation: Dust and Mists)

Skin corrosion/irritation : No data.

Serious eye damage/eye irritation : No data.

Respiratory or skin sensitization : No data.

Germ cell mutagenicity : Although there are contradicting results about the

chromosome aberration in the peripheral blood lymphocytes from people who are engaged in lead-related work (IARC suppl.7 (1987), EHC 3 (1977), DFGOTvol.17 (2002), ACGIH (7th, 2001)), there are descriptions of lead itself having chromosome aberration/micronucleus inductive actions.

Therefore, it was classified as Category 2.

Carcinogenicity : From the below classifications, it was classified as Category

2.

 IARC Supplement 7 (1987) and Japan Society for Occupational Health: 2B

• ACGIH (7th, 2001): A3

• EPA (IRIS (1993)): B2

Reproductive toxicity : Since there is the description that there is the affect for

sperm formation disorder in human exposure example (EHC 3 (1977), ACGIH (7th, 2001), DFGOTvol.17 (2002)), and ovulation dysfunction was observed in the female occupation exposure example (EHC 3 (1977)), it was classified as "Category 1A". There are the descriptions about the relationship with neonatal developmental disorder of

cognitive function (ACGIH (7th, 2001), DFGOTvol.17 (2002),

PATTY (4th, 1994) and IARC 23 (1980)), and the descriptions about the relationship with the increase of miscarriage (DFGOTvol.17 (2002), and PATTY (4th, 1994)).

However, the distinct conclusion has not obtained.

Specific target organ toxicity : Although there was a case report that renal dysfunction was

observed in the acute toxicity in human (DFGOT, vol.17 (2002)), there was the description that no kidney damage in

(single exposure)

Product name: Small-sized valve regulated lead-acid battery(non-Flame retardant)

Company name: GS Yuasa International Ltd.

Page 8 / 19

Date of issuing: 2018/2/7 Date of revision: 2020/4/20

Latest confirmation date: 2020/4/20

the subsequent epidemiologic study in the same source of reference. Therefore, the data is insufficient for considering the kidney as target organ, therefore, it is classified as

"classification not possible".

Specific target organ toxicity (repeated exposure) : Due to the descriptions that the target organs were hematopoietic system, nervous system, kidney, and cardiovascular system in DFGOTvol.17 (2002), that heme synthesis inhibitors, nephropathy and brain diseases were observed in the human exposure examples in EHC 3 (1977), ACGIH (7th, 2001), PATTY (4th, 1994), and IARC 23 (1980), that it affects to the peripheral nerve and function of central nerve system in humans exposure examples in EHC 3 (1977), ACGIH (7th, 2001), PATTY (4th, 1994), that it affects to cardiovascular system, such as high blood pressure in human exposure examples in EHC 3 (1977), ACGIH (7th, 2001), that the immunosupressive effect was observed in human exposure examples in PATTY (4th, 1994), it is considered that the target organs were hematopoietic system, the kidney, central nervous systems, peripheral nervous system, cardiovascular system and immune system, and they all were classified as "Category 1". Although there are the descriptions of the case reports of thyroid or adrenal hypofunctions in EHC 3 (1977), each case reports are before 1970, and there is no similar report after that, since there is the description that no effects was observed in the thyroid in DFGOTvol.17 (2002), the thyroid and the adrenal gland were not considered as for target organs.

Aspiration hazard : No data.

Others : No information.

OLead dioxide (electrode plate)

Acute toxicity (Oral) : No data. Acute toxicity (Dermal) : No data.

Acute toxicity (Inhalation: Gases) : Classification not applicable because it is a solid in the

definition of GHS.

Acute toxicity (Inhalation: Vapours) : No data.

: No data. Acute toxicity

(Inhalation: Dust and Mists) Skin corrosion/irritation

: Since there is the description of "Probably a severe eye, skin, and mucous membrane irritant "(HSDB (2006)), it is considered that indicate severe irritation to skin. Therefore, it was classified as Category 2.

Serious eye damage/eye irritation

: Since there is the description of "Probably a severe eye, skin, and mucous membrane irritant "(HSDB (2006)), it is considered that indicate severe irritation to eyes. Therefore,

Product name: Small-sized valve regulated lead-acid battery(non-Flame retardant)

Company name: GS Yuasa International Ltd.

Page 9 / 19

Date of issuing: 2018/2/7 Date of revision: 2020/4/20

Latest confirmation date: 2020/4/20

it is classified as Category 2A.

Respiratory or skin sensitization Germ cell mutagenicity : No data.

: From the description of NTP DB (Access on February 2006);

- Heritable germ cell mutagenicity tests: None.
- Germ cell/ somatic cells in vivo mutagenicity tests:
 None
- Germ cell/ somatic cells in vivo genetic toxicity test:
 None.
- Positive (strong) results of multiple indicators in in vitro mutagenicity test: None.

It was classified as "Classification not possible".

: From the below classifications, it was classified as Category

• NTP (2005): R

IARC (1987): Group 2B

ACGIH (2001): A3

The Japan Society for Occupational Health: 2B

: Since lead is known as neurotoxic substance and reproductive toxic substance for human, it is classified as "Category 1A" based on experts' judgement.

: For this substance, it is assumed that the classification based on the effects of inorganic lead compounds.

As the toxicity of inorganic lead compounds for humans, there is the description below;

"acute effects and chronic effects of inorganic lead has been recognized almost the same symptoms. By inhalation or ingestion of inorganic lead, it has been reported that cause the convergence of the mouth, thirst. And also nausea, vomiting, upper abdominal discomfort, loss of appetite, abdominal pain, constipation and the like has been reported as effects on the digestive organs.

Effects on hematopoiesis are typical effects of inorganic lead, it has been observed hemoglobin synthesis inhibition and anemia due to shortened of red blood cell life, caused by inhibition of δ -aminolevulinic acid and heme synthesis enzyme. Interstitial nephropathy as the effect to the kidneys, in addition to decreasing amount of urine, proteinuria, hematuria, urine cylinder, the proximal tubule disorder exhibiting a Fanconi syndrome typified by diabetes and amino acid urine is reported. Inorganic lead affects on the peripheral nervous system, in particular, muscle weakness in limbs, pain and convulsions are observed. In addition, although it is very rare case in adults, in case of being exposed to extremely high concentrations (details unknown), the effects on the central nervous system are observed such as ataxia, headache, paresthesia, depression and coma.

Carcinogenicity

Reproductive toxicity

Specific target organ toxicity
(single exposure, repeated exposure)

Product name: Small-sized valve regulated lead-acid battery(non-Flame retardant)

Company name: GS Yuasa International Ltd.

Page 10 / 19

Date of issuing: 2018/2/7 Date of revision: 2020/4/20

Latest confirmation date: 2020/4/20

However, in effects on the central nervous system, particularly sensitive in children, and the symptoms with no restless, aggressive personality, difficulty concentrating, decline of memory and the like have become a problem in the U.S." (CERI Hazard Assessment Report 2001-9(2002)) Therefore, blood system, kidney and nervous system are considered to be target organs. From the above, it was classified as "Category 1(blood system, kidney, nervous system)".

Aspiration hazard : No data.

Others : No information.

OLead sulfate (electrode plates)

Acute toxicity (Oral) : No data. : No data. Acute toxicity (Dermal)

Acute toxicity (Inhalation: Gases) : Classification not applicable because it is a solid in the

definition of GHS.

Acute toxicity (Inhalation: Vapours) : No data.

: No data. Acute toxicity

(Inhalation: Dust and Mists)

Skin corrosion/irritation : No data. As effects on humans, although there is no data that can be obtained for local effects on the skin and mucous

membranes by lead and inorganic lead compounds, there is the description of that there is likely to cause severe irritation

and burns to the skin.

: No data. As effects on humans, although there is no data Serious eye damage/eye irritation

> indicating the local effects on the mucous membranes by lead and inorganic lead compounds, there is the description of that there is likely to cause severe irritation and burns to

the eye.

Respiratory or skin sensitization

: No data.

Germ cell mutagenicity : It is "Classification not possible" due to insufficient data of in

> vivo test. In addition, in the in vitro test, there is the negative report in Ames test. Moreover, although it may not be necessarily matched results have been obtained, there is also the positive result in chromosome analysis using peripheral blood of workers who received the occupational exposure of lead. However, the used method is insufficient in most of the tests, overall it stated that it cannot be conclusive

evaluation of genotoxicity in human. Inorganic lead

compounds in MAK / BAT (2010) are classified as germ cell

mutagenicity 3A.

Carcinogenicity : In carcinogenicity evaluation of IARC, it is classified as

Group 2A as inorganic compounds. Therefore, this

substance was classified as Category 1B. In addition, it is

Product name: Small-sized valve regulated lead-acid battery(non-Flame retardant)

Company name: GS Yuasa International Ltd.

Page 11 / 19

Date of issuing: 2018/2/7 Date of revision: 2020/4/20

Latest confirmation date: 2020/4/20

classified as 2B as a lead compound in The Japan Society for Occupational Health, and A3 as inorganic lead compound in ACGIH.

Reproductive toxicity

: Although there is no data of this substance, as effect on humans of inorganic lead compounds, an increase in the spontaneous abortion of pregnancy before 20 weeks was observed by a high concentration exposure of mothers in cases or epidemiological studies.

There is description that exposure during the pregnancy is related increased in teratogenicity, low weight newborns and suppression of body weight gain after birth.

Although decrease in sperm count and semen volume, morphological changes of sperm, and decreasing of sperm motility were observed by the occupational exposure, in most studies, it is observed dose-response relationship between these effects and exposure concentration of lead, and toxicity for sperm has been reported to have been unclear.

Specific target organ toxicity (single exposure)

: Although there is no data of this substance, neurotoxic effect of lead is known, and receives the influence of the lead in both the peripheral nerves and the central nervous system. Lead encephalopathy is one of the early symptoms of acute exposure. From also that there is a report of the suppression of the pituitary hands and nerve conduction velocity by the occupational exposure, it is classified as "Category 1 (nervous system)". In high concentration acute exposure of lead and inorganic lead compounds, it causes dysfunction of the proximal tubule. There is the description that it causes Fanconi syndrome (diabetes, amino acid urine disease, phosphate urine disease and the like) as renal symptoms of acute lead poisoning. Therefore, it was classified as "Category 1 (kidney)".

Moreover, lead is also known to give a change in the blood system. There is the description that the hemoglobin synthesis inhibition and small blood cell anemia and hypochromic anemia due to shortened of red blood cell life are caused by δ -aminolevulinic acid and heme synthesis enzyme are inhibited. Therefore, it is classified as "Category 1 (blood system)".

Other, colic is the initial symptoms of occupational exposure or high concentration acute exposure. Since there is the description of the associated symptoms such as constipation, severe abdominal pain, nausea, vomiting, loss of appetite, it is classified as "Category 1 (digestive system)". Although there is no data of the substance, there is the description that in high concentration repeated exposure by

Specific target organ toxicity (repeated exposure)

Product name: Small-sized valve regulated lead-acid battery(non-Flame retardant)

Company name: GS Yuasa International Ltd.

Page 12 / 19

Date of issuing: 2018/2/7 Date of revision: 2020/4/20

Latest confirmation date: 2020/4/20

lead and inorganic lead compounds, it leads to irreversible changes to kidney including tubular atrophy, interstitial fibrosis glomerular sclerosis, and eventually it cause chronic nephritis. Therefore, it was classified as "Category 1(kidney)".

In addition, there is the report of the lead epidemiological study, hemoglobin concentration and hematocrit value of poisoning patients were significantly decreased compared with control subjects of non-exposure.

There is the description that the hemoglobin synthesis inhibition and small blood cell anemia and hypochromic anemia due to shortened of red blood cell life are caused by δ -aminolevulinic acid and heme synthesis enzyme are inhibited. Therefore, it was classified as "Category 1 (blood system)".

On the other hand, there is the research study to support the relationship between the chronic lead poisoning and myocardial injury, and there is reported that abnormal electrocardiogram in workers of lead poisoning was observed. In addition, from the data of epidemiological studies, since it has been concluded that internal absorption of lead causes a significant increase in blood pressure in both diastolic and systolic of the heart, it was classified as Category 1(cardiovascular).

Moreover, suppression of motor nerve conduction velocity was observed in worker who blood concentration of lead is high, and also there is a report of the Parkinson's syndrome has been observed in seven out of nine that have been exposed for more than 30 years in a lead-acid battery. Therefore, it was classified as "Category 1(nervous system)".

Aspiration hazard : No data.

Others : No information.

ODilute sulfuric acid (electrolyte)

Acute toxicity (Oral)

: Based on the Rat LD₅₀ value: 2140mg/kg and the description of the death case report by the oral ingestion in humans (amount of intake is unknown), it was classified as Category 5 ("Not classified" by JIS classification).

Acute toxicity (Dermal) : No data.

Acute toxicity (Inhalation: Gases) : Classification not applicable because it is a liquid in the

definition of GHS.

Acute toxicity (Inhalation: Vapours) : No data.

Acute toxicity

(Inhalation: Dust and Mists)

: Based on rat LC₅₀ value: 0.375mg/L (4 hour exposure) and 347ppm (1-hour exposure) (4 hour equivalent value:

Product name: Small-sized valve regulated lead-acid battery(non-Flame retardant)

Company name: GS Yuasa International Ltd.

Page 13 / 19

Date of issuing: 2018/2/7 Date of revision: 2020/4/20

Latest confirmation date: 2020/4/20

0.347mg/L), it was classified as Category 2.

Skin corrosion/irritation : Since pH of concentrated sulfuric acid was 1 or less, it was

> judged to be corrosive substance in accordance with the GHS classification standards, and classified as Category

1A-1C.

Serious eye damage/eye irritation : There is the description that the critical damage to the eye

> accompanied by lysis of anterior chamber of eye was observed in accident case of human. And also from the description that the moderate irritation with 5% solution and the severe irritation with 10% solution were observed to the eye of rabbit, therefore, it was classified as "Category 1".

: Respiratory sensitization: No data.

Skin sensitization:

There is no test data on skin sensitizing of sulfuric acids. Although sulfuric acid has been industrially used for several decades, there is no case report of skin sensitization while skin injuries by skin irritation are well known.

Although an extensive amount of sulfate ion exists internally (the sulfate ion in serum ~33 mmol/L, and 50 times more in cells), allergic reactions do not occur.

In allergic test of sulfuric acid salt of metal, even if allergic positive with metal may occur, sulfuric ion is presumed to result in allergic negative as is suggested by the negative results in sulfate of zinc. Based on the description that conclusion is obtained from the results mentioned above that sulfate does not cause allergy to human, it is classified as "Not classified".

: For in vivo, there is not any test data which the reproductive cells and the somatic cells were used. For in vitro

mutagenicity tests, there is the positive result only in the test system with the single indicator (chromosomal aberration test). However, there are negative results in other indices. Therefore, it was classified as "Classification not possible".

: Occupational exposure of the mist of the inorganic strong

acid including sulfuric acids is classified as group 1 according to IARC, as A2 according to ACGIH, and as K

according to NTP.

Respect the evaluation of IARC and the latest NTP, it was classified as category 1. However, sulfuric acids itself was classified as the category 4 according to DFGOT. And, since none of those institutions have carried out the carcinogenic classification, it was classified as "Classification not

possible".

: In inhalation exposure test using rabbit and mouse in fetal

organogenesis period, it is not observed of fetotoxicity and teratogenicity at the dose causing no maternal toxicity in

Respiratory or skin sensitization

Germ cell mutagenicity

Carcinogenicity

Reproductive toxicity

Product name: Small-sized valve regulated lead-acid battery(non-Flame retardant)

Company name: GS Yuasa International Ltd.

Page 14 / 19

Date of issuing: 2018/2/7 Date of revision: 2020/4/20

Latest confirmation date: 2020/4/20

both species. And also, the effect on the reproductive organ of both sexes is not observed in chronic toxicity test and

carcinogenicity test. Since the direct effect by

irritation/corrosive is the main toxicity, it is judged that there is no concern that indicates the reproductive toxicity,

therefore, it was classified as "Not classified".

Specific target organ toxicity

(single exposure)

: There is the descriptions that in the inhalation exposure of low concentration in humans, airway irritation symptoms such as cough and breath shortness are observed and at high concentration exposure, addition to acute effects such as cough, breath shortness and hemoptysis shedding etc., permanent effects such as functional depression of lungs, fibrosis and emphysema are observed. Additionally, there is the description that hemorrhage and dysfunction in lungs were observed in 8-hour inhalation exposure using guinea pigs. Based on these descriptions, it was classified as "Category 1 (respiratory systems)".

Specific target organ toxicity

(repeated exposure)

: In the 28-day inhalation exposure test using rat, cell proliferation in laryngeal mucosa is observed in guidance value range of Category 1. In the 14 to 139-day repeated inhalation exposure test using the guinea pigs, respiratory and lung disorder, such as nasal-septum dropsy, pulmonary emphysema, atelectasis, hyperemia, dropsy, bleeding and thrombosis of bronchioles are observed at the concentration range of guidance value of Category 1. Furthermore, in the 78-week inhalation exposure test using a cynomolgus, histological change as hyperplasia of a cell, the wall thickening, etc. in bronchioles of lungs were observed at the dosage (0.048 mg/L, 23.5 Hr/Day) of the guidance value range of Category 1. From the above, it was classified as Category 1 (respiratory systems).

Aspiration hazard : No data.

Others : No information.

12. Ecological Information

Indicate the information for each of components of lead acid battery as below.

OLead (electrode plate, terminal)

Ecotoxicity : No data.

Persistence/degradability : No data.

Bioaccumulation : No data.

Mobility in soil : No information.

Hazardous to the ozone layer : Not contain ingredients listed in the Annex of the Montreal

Protocol.

Product name: Small-sized valve regulated lead-acid battery(non-Flame retardant)

Company name: GS Yuasa International Ltd.

Page 15 / 19

Date of issuing: 2018/2/7 Date of revision: 2020/4/20

Latest confirmation date: 2020/4/20

OLead dioxide (electrode plate)

Ecotoxicity : No data.

Persistence/degradability : No data.

Bioaccumulation : No data.

Mobility in soil : No information.

Hazardous to the ozone layer : Not contain ingredients listed in the Annex of the Montreal

Protocol.

OLead sulfate

Ecotoxicity : Crustacean: Daphnia magna, 48hr-IC₅₀ = 0.5mg/L

(Acute hazardous to the aquatic environment: Category 1) Reliable chronic toxicity data has not been obtained. Since it is metal compound, the behavior in water is not known. Because acute toxicity is category 1, chronic hazardous to the aquatic environment was classified as "Category 1".

Persistence/degradability : No data.

Bioaccumulation : No data.

Mobility in soil : No information.

Hazardous to the ozone layer : Not contain ingredients listed in the Annex of the Montreal

Protocol.

ODilute sulfuric acid (electrolyte)

Ecotoxicity : Fishes: Bluegill, 96hr-LC₅₀ = 16-28mg/L

(Acute hazardous to the aquatic environment: Category 3) Toxicity factor is considered to be aqueous solution which becomes strong acid, but toxic effect is eased by the buffer action in the environmental water. Therefore, Chronic hazardous to the aquatic environment was classified as "Not

classified".

Persistence/degradability : No data.
Bioaccumulation : No data.
Mobility in soil : No data.

Hazardous to the ozone layer : Not contain ingredients listed in the Annex of the Montreal

Protocol.

13. Precautions for Disposal

Disposal considerations : In the disposal, follow "Waste Management and Public

Cleansing Law" and the standards of the local government. Entrust disposal to industrial waste disposal contractor who have obtained a license from local governor, otherwise if the local government is performing waste disposal, entrust them

disposal.

14. Transport Information

Company name: GS Yuasa International Ltd.

Page 16 / 19

Date of issuing: 2018/2/7 Date of revision: 2020/4/20

Latest confirmation date: 2020/4/20

GOODS. But the battery does not correspond to dangerous goods because it satisfied SPECIAL PROVISIONS.

Valve regulated lead-acid battery corresponds to an escape Clause A67 of dangerous goods in IATA.

Therefore, the battery does not correspond to dangerous goods.

Indicate the information for transport restrictions as below.

International regulations(dangerous goods)

Inland transport : Follow the regulation under ADR/RID. Sea transport : Follow the regulation under IMO. Air transport : Follow the regulation under ICAO/IATA.

: 2800 **UN** number

: Corrosive substance/Class 8 **UN class**

Proper shipping name : BATTERIES, WET, NON-SPILLABLE, electric storage

Packing group : -

Special requirements : IMO SP29, SP238

IATA A48, A67, A164

: Not applicable Marine pollutant

Japan domestic regulations

: Follow the regulation of Fire Service Act and Poisonous and Inland transport

Deleterious Substances Control Law.

: Follow the regulation of Ship Safety Law. Sea transport : Follow the regulation of Civil Aeronautics Act. Air transport

Special safety measures and condition

for transport

: Avoid mixed load with other substances as much as possible.

Handle the dilute sulfuric acid so as not to leak by

overturning or falling.

Load to not overturning, falling and damage, and take

prevention of cargo collapse securely.

Avoid transport under the direct sunlight and high

temperature.

Transport in accordance with the standards of other related

laws and regulations.

Emergency guideline : 154 response

number(North America)

HS code

: 8507.20 (Lead-acid batteries(except for starting piston

engines))

Country of origin : Marked on the product.

15. Regulatory Information

There are not laws and regulations applicable for the lead-acid battery itself.

Describe the information about the components below.

Industrial Safety and Health Act : Dangerous and Harmful Substances Subject to Indicate

Their Names (Article 57 of the Act)

Lead components: lead dioxide, lead sulfate

Product name: Small-sized valve regulated lead-acid battery(non-Flame retardant)

Company name: GS Yuasa International Ltd.

Page 17 / 19

Date of issuing: 2018/2/7 Date of revision: 2020/4/20

Latest confirmation date: 2020/4/20

Dangerous and Harmful Substances Subject to Notify Their Names (Article 57-2 of the Act)

- Lead and its inorganic compounds: lead, lead dioxide, lead sulfate
- Sulfuric acid: dilute sulfuric acid.

Corrosive liquids (Article 326 of the regulation)

- Sulfuric acid: dilute sulfuric acid

Specified Chemical Substances (Article 2 of The Ordinance on Prevention of Dangers Due to Specified Chemical Substances, paragraph 1)

Category 3 substance

- Sulfuric acid: dilute sulfuric acid

Lead (Appended Table 4 of the Enforcement Ordinance No.1 of Article 1 of the Ordinance on Prevention of Lead Poisoning.)

- Lead

Lead compounds (Appended Table 4 of the Enforcement Ordinance No. 4 of Article 1 of the Ordinance on Prevention of Lead Poisoning.)

- Lead dioxide, Lead sulfate

: Illness chemical substances (Article 75 of the Act, paragraph 2, article 35 of the Enforcement Regulations, Appended table of 1-2, no.4)

Lead and its compounds
 Lead, lead dioxide, lead sulfate

Poisonous and Deleterious Substances Control Act

Labor Standards Act

: Deleterious Substances (Article 2 of the designated ordinance)

- Lead compounds: lead dioxide
- Sulfuric acid: dilute sulfuric acid

Act on Confirmation, etc. of Release Amounts of Specific Chemical Substances in the Environment and Promotion of Improvements to the Management Thereof : Class I Designated Chemical Substances (Paragraph 2 of Article 2 of the Act, Appended Table 1 of Article 1 of the Enforcement Ordinance)

- Lead

Specified Class I Designated Chemical Substances (Paragraph 2 of Article 2 of the Act, Article 4 of the Enforcement Ordinance)

- Lead compounds: lead dioxide, lead sulfate : Hazardous material Category 1 Oxidizing solid

- Chromium, lead or oxide of iodine
- Lead dioxide

: Substances Inhibiting Fire Fighting

- Lead dioxide
- Sulfuric acid: dilute sulfuric acid

Marine Pollution Prevention Law

Fire Service Act

: Noxious liquid substances

- Category Y: Dilute sulfuric acid

Civil Aeronautics Act : Article 194 of Enforcement Regulations, Appended Table 1

Company name: GS Yuasa International Ltd.

Page 18 / 19

Date of issuing: 2018/2/7 Date of revision: 2020/4/20

Latest confirmation date: 2020/4/20

of the Notification for Establishing Standards for the Carriage of Dangerous Goods in Ships

- Oxidizing substances: lead dioxide
- Corrosive substance: lead sulfate (which the content of free acid is more than 3 wt%)
- Corrosive substance: dilute sulfuric acid

Ship Safety Act

: Article 2,3 of the Dangerous Goods Regulations, Appended Table 1 of the Notification for Establishing Standards for the Carriage of Dangerous Goods in Ships

- Oxidizing substances: lead dioxide
- Corrosive substance: lead sulfate (which the content of free acid is more than 3 wt%)
- Corrosive substances: dilute sulfuric acid

Water Pollution Prevention Act

: Noxious Substances (No.1 of Paragraph 2 of Article 2 of the Act)

- Lead and its compounds:

Lead, lead dioxide, lead sulfate

: Designated Substances (Paragraph 4 of Article 2 of the Act)

Sulfuric acid: dilute sulfuric acid

Act on Port Regulations

- Oxidizing Substances: lead dioxide
- Corrosive Substance: lead sulfate (which the content of free acid is more than 3 wt%)
- Corrosive Substances: dilute sulfuric acid

16. RoHS Instruction

Lead and lead compound contained in the lead-acid battery are off the subject of the RoHS instruction.

17. Other Information

Electrochemical reaction formula:

Positive Electrolyte Negative Positive Electrolyte Negative PbO_2 2H₂SO₄ + Pb Charge<---->Discharge PbSO₄ 2H₂OPbSO₄ Lead Dioxide Sulfuric Acid Lead Lead sulfate Water Lead sulfate

(Land transportation In U.S.A and Canada)

According to law by Department of Transportation(DOT), "NONSPILLABLE" or "NONSPILLABLE BATTERY" must be described on battery or package in order to call the attention of nature of transport goods to the drivers.

(TSCA)

Ingredients in GS Yuasa batteries are listed in the TSCA registry as follows:

Components		CAS number	TSCA status	
Electrolyte	Sulfuric Acid (H ₂ SO ₄)	7664-93-9	listed	
Inorganic lead	lead (Pb)	7439-92-1	listed	

Company name: GS Yuasa International Ltd.

Page 19 / 19

Date of issuing: 2018/2/7 Date of revision: 2020/4/20

Latest confirmation date: 2020/4/20

compound	Lead dioxide (PbO ₂)	1309-60-0	listed
	Lead sulfate (PbSO ₄)	7446-14-2	listed
	Calcium (Ca)	7440-70-2	listed
	Tin (Sn)	7440-31-5	listed
	Barium (Ba)	7440-39-3	listed

(California Proposition 65)

Battery posts, terminals and related accessories contain lead and lead compounds, and other chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. Wash hands after handling.

Reference:

Globally Harmonized System of classification and labelling of chemicals, (5th ed., 2013), UN JIS Z 7253:2012

- 1) NITE GHS classification data.
- 2) ECHA Home page (http://echa.europa.eu/information-on-chemicals)
- 3) NITE CHRIP (http://www.safe.nite.go.jp/japan/sougou/view/SystemTop_jp.faces)

Notice:

The contents described in this sheet are prepared based on the data and information currently available to us. However, it does not intend to be any guarantees in regard to content, physical and chemical properties, hazards, etc.

Please handle this product in the responsibility of the user after referring to this sheet.

In addition, the precautions are intended for normal handling. Please use under implementing safety measures that are suitable for application/usage if you want to special handling.