PRODUCT INFORMATION SHEET

Lead-acid battery is not a target product for SDS (safety data sheet). This sheet is intended to be issued in order to provide "reference information" to ensure the safe handling of the product.

Product name	: Vent type lead-acid battery HS, PS, SS(paste type)
Information on company	
Company name	: GS Yuasa International Ltd.
Relevant dept.	: Industrial Battery Production Division Industrial Batteries & Power Sources Business Unit
Address	: 1,Inobanba-cho,Nishinosho,Kisshoin,Minami-ku,Kyoto,601-8520,Japa
Phone number	:81-75-316-3619
Fax number	:81-75-312-0379

2. Hazards Identification

GHS classification	
Physical and chemical hazards	: Not applicable
Health hazards	: Not applicable
Environmental hazards	: Not applicable
GHS label elements:	
Pictogram	: None
Signal words	: None
Hazard statements	: None
Precautionary statement	: None
Other risks/hazards	: No information

3. Composition/Information on Ingredients

Information on composition and ingredients:

morma	normation on composition and ingredients.				
NO.	Chemical name or common name	Component part	Content rate (mass ratio)	Chemical formula	CAS no.
	Lead, Lead compounds	Terminal,		Pb	7439-92-1
1	(Lead dioxide, Lead		50-65%	PbO ₂	1309-60-0
	sulphate etc.	electrode plate		PbSO ₄	7446-14-2
2	Antimony	electrode plate	1-2%	Sb	7440-36-0
3	Arsenic	electrode plate	0.1% or below	As	7440-38-2
4	Barium compound	electrode plate	0.2% or below	BaSO ₄	7727-43-7
5	Dilute sulfuric acid		20,40%		7664 02 0
5	(abt. 30%)	Electrolyte	30-40%	H ₂ SO ₄	7664-93-9
6	AS resin, ABS resin	Battery container, lid	4-8%	—	9003-56-9(ABS)

7	PS resin, PVC resin(%) (%)PS-1320 over, TYPE)	Spacer	2-3%	_	_
8	Glass	Separator	0.2-0.5%	_	—
9	PE resin, PP resin, silica, epoxy resin, rubber	Other resin parts	1% or below	_	9003-07-0(PP)
10	Brass etc.	Other metal parts	1% or below	_	_

First-aid Measures	
If inhaled	: (Lead, lead dioxide, lead sulfate, dilute sulfuric acid)
	Remove person to fresh air, keep comfortable for
	breathing.
	Get medical advice/attention.
If on skin	: (Lead, lead dioxide, lead sulfate)
	Wash skin with plenty of water and soap.
	If skin irritation occurs, get medical advice/attention.
	(dilute sulfuric acid)
	Take off or remove immediately all contaminated clothing
	Rinse skin with water or shower.
	If skin irritation or chemical injury occurs, get medical
	advice/attention.
If in eyes	: (Lead, lead dioxide, lead sulfate, dilute sulfuric acid)
	Open the eyelids with your fingers, rinse thoroughly with
	water for at least 15 minutes.
	Remove contact lenses, if present and easy to do.
	Continue rinsing.
	Get medical attention/advice.
If swallowed	: (Lead, lead dioxide, lead sulfate)
	Rinse mouth.
	Get medical advice/attention.
	(dilute sulfuric acid)
	Rinse mouth.
	Give plenty of water.
	Do not induce vomiting.
	Get medical advice/attention.
Most important symptoms/effects,	: (Lead, lead dioxide, lead sulfate)
acute and delayed	Stomach cramps, lethargy, headache, nausea, vomiting, weakness, wheezing, pallor, hemoglobinuria, collapse.
	(dilute sulfuric acid)
	Corrosive, burning sensation, sore throat, cough,
	breathlessness, shortness of breath, redness, pain,

	No.PIS18-0009B Product name: Vent type lead-acid battery(paste type) Company name: GS Yuasa International Ltd. Page 3 / 19 Date of issuing: 2018/2/7 Date of revision: 2020/4/20 Latest confirmation date: 2020/4/20 blisters, severe skin burns, severe burns, abdominal pain, shock or collapse.
Protection for first-aiders	: Rescuers wear protective equipment such as rubber gloves and tight-fitting safety goggles.
Special note to physician	 : (Dilute sulfuric acid) Symptoms of lung edema often do not show until a few hours have passed, and it might aggravate if it does not take a rest. Therefore, it is necessary to take a rest and medical observation.

Suitable extinguishing media	: Extinguish the fire by extinguishers of dry chemical agent,
	foam fire extinguish agent, and non-flammable gas.
Unsuitable extinguishing media	: No information.
Specific risk/hazard	: In case of fire, there is a possibility that irritative, corrosive or toxic fumes or gases are generated.
	There is a possibility of explosion of the product by heat.
Specific fire fighting method	 : Cut off the power in case of connection/energizing the product into the device, if can be coped with safely. Move the product from the fire area if it is not dangerous. After extinguishing the fire, continue to cool the container thoroughly with plenty of water. Immediately move the movable product to safe place when fire occurs in surrounding. If it is not movable, cool the product with water spray. Keep away the combustible materials to prevent spread fire around.
Protection for fire-fighters	: Extinguish fire from upwind. Wear appropriate protective clothes for chemical (self- contained breathing apparatus, protective glasses, etc.) to fire fighting.

6. Accidental Release Measures

Personal precautions, protective	: Wear appropriate protective equipment (gloves, protective
equipment and emergency measures	glasses, protective clothing and the like), when processing
	the leakage.
	Do not touch or walk through the leakage.
	Do not breathe dust, mist and vapour.
Precautions for the environment	: Be careful to not discharge the product into the rivers, sewer, and soil.
·····	
Method for containment and clean-up	: If dilute sulfuric acid is leaked, stopping the flow with sand
	and earth, absorbing mat and the like, remove by absorbing
	with them. And then, neutralized with sodium bicarbonate or
	slaked lime, and wash off with plenty of water.

	No.PIS18-0009B Product name: Vent type lead-acid battery(paste type) Company name: GS Yuasa International Ltd. Page 4 / 19 Date of issuing: 2018/2/7 Date of revision: 2020/4/20 Latest confirmation date: 2020/4/20
	Absorb by sprinkling misty water when the gas is generated.
	Collected material should be disposed in compliance
	with '13. Disposal Considerations'.
Prevention of secondary hazards	: Immediately remove all ignition sources in the vicinity.
	Prepare fire extinguishing equipment just in case it is
	ignited.

Handling	
Technical measures	: Take measure described in '8: Exposure Controls and Personal Protective Equipment', and wear appropriate protective equipment.
Local exhaust/general ventilation	: Work in a well-ventilated place and provide local exhaust or general ventilation as necessary.
Cautions for Safety Handling	: Do not use fire near the product.
	Do not dismantle or modify the product.
	Do not do short-circuit between the terminals.
	Handling and charging of the product should be in well ventilated place.
	Prevent falling and overturning of container. Careful to not give a shock.
	Try to not damage the product.
	Be careful that there is a possibility of spewing dilute sulfur acid from the vent plug of product when open.
	Be careful not to spill the dilute sulfuric acid.
	Do not eat, drink or smoke when using this product.
Storage	
Technical measures	: Provide a ventilation and lighting required for storing and handling hazardous materials in the storage location.
Storage condition	: Do not store near the fire.
	Do not store in place where is exposed to high temperatur high humidity, rain, direct sunlight.
	Store in place where is no risk of fire, toxic gas, liquid
	droplets, generating or invasion of dust, and submerged.

Controlled exposure level	: Lead (electrode plate, terminal), lead dioxide(electrode
	plate), lead sulfate(electrode plate)
	Lead and its compounds(as lead)
	$TLV = 0.05 \text{ mg/m}^3$
Permissible exposure level	
Japan Society for Occupational	: Lead(electrode plate, terminal), lead dioxide(electrode
Health (2014)	plate), lead sulfate(electrode plate)
	Lead and its compounds(as lead) : TLV = 0.1 mg/m^3

	No.PIS18-0009B Product name: Vent type lead-acid battery(paste type) Company name: GS Yuasa International Ltd. Page 5 / 19
	Date of issuing: 2018/2/7 Date of revision: 2020/4/20 Latest confirmation date: 2020/4/20
	Dilute sulfuric acid(electrolyte)
	Sulfuric acid: Maximum permissible exposure limit =
	1mg/m ³
ACGIH (2014)	: Lead(electrode plate, terminal), lead dioxide(electrode
	plate),lead sulfate(electrode plate)
	LEAD AND INORGANIC COMPOUNDS, AS Pb
	TLV-TWA = 0.05 mg/m ³
	Dilute sulfuric acid(electrolyte)
	Sulfuric acid: TLV-TWA = 0.2mg/m ³
Engineering controls	: Provide hand wash and eyes wash facilities and safety
	shower near the handling place as necessary.
Personal protective equipment	
Respiratory protection	: Wear respiratory protective equipment (air respirator, dust
	mask, gas mask (for acid gases)) as necessary.
Hand protection	: Wear impermeable protective gloves (acid resistance).
Eye protection	: Wear protective glasses, goggle type safety glasses and the like.
Skin and body protection	: Wear protective clothing, protective apron and the like as necessary.
Hygiene measures	: Do not eat, drink or smoke when handling.
	Wash hands thoroughly after handling.
	Protective equipment shall be inspected regularly according
	to the protective equipment checklist.

9. Physical and Chemical properties

Describes the information about the components below.

	Lead	Lead dioxide	Lead sulfate	Dilute sulfuric acid
Appearances (physical state, form, color, etc.)	Silver white solid	Brown crystal or powder	White crystal	Colorless transparent liquid
Odor	No information.	No information.	No information.	Odorless (normal temperature)
Threshold of odor	No information.	No information.	No information.	No information.
рН	No information.	No information.	No information.	≦1
Melting point	327.4°C	888°C	1170°C	\leq -40°C(s.g.1.30)
Boiling point, initial boiling point and boiling range	1,749°C	1,480°C	No information	114°C(s.g.1.30)
Flash point	Non flammable	Non flammable	Non flammable	Non flammable
Flammability(solid, gas)	Non flammable	Non flammable	Non flammable	Not applicable
Specific gravity(density)	11.35g/cm ³ (20°C)	9.53g/cm ³	6.2	Approx. 1.2~1.4

			Latest confin	mation date: 2020/4/20
Solubility	Water: Insoluble.	Water: Insoluble.	Water: Hardly	Miscible in water.
			soluble.	Soluble in alcohol.
Partition coefficient (n-	No information.	No information	No information	No information
octanol/water)				
Auto-ignition	Non flammable	Non flammable	Non flammable	Non flammable
temperature				
Decomposition	No information.	290°C	1000°C	No information
temperature				
Viscosity	No information.	No information.	No information.	No information.
Other Information	No information.	No information.	No information.	No information.

). Stability and Reactivity	
Stability	: (lead)
	When oxygen is present, it will be eroded by pure water
	and the weak organic acid. At normal temperature, it will be
	eroded by fluorine or chlorine.
	(lead dioxide/ lead sulfate)
	It is considered to be stable under normal handling and
	storage.
	(dilute sulfuric acid)
	At first, vapor is generated by heating, and generate
	sulfuric acid vapors if continue to heat.
	Rapid contact with water might be generate a large amour
	of heat, and sometimes the acid is scattered.
	Dilute sulfuric acid which is generated by diluting with
	water, generates hydrogen gas by the corrosion of various
	metals and may cause flash explosion by mixing with air.
	There is hygroscopic.
Hazardous reactivity	: (lead)
	It does not occur hazardous reaction under normal
	condition.
	(lead dioxide)
	React violently with combustible materials and organic
	matter (sulfuric acid, hydrogen peroxide, phosphoric acid),
	and it may cause risk of fire.
	(lead sulfate)
	It may react with strong oxidizing agents.
	(dilute sulfuric acid)
	It may cause fire or explosion by many reactions.
	It is strong oxidant and reacts with combustible and
	reducing materials.
	It is strong acid and reacts violently with bases and is
	corrosive to most common metals forming a
	flammable/explosive gas(hydrogen).

	No.PIS18-0009B Product name: Vent type lead-acid battery(paste type) Company name: GS Yuasa International Ltd. Page 7 / 19 Date of issuing: 2018/2/7 Date of revision: 2020/4/20 Latest confirmation date: 2020/4/20 React with water and organic materials violently and release heat.
Conditions to avoid	: Heating, contact with ignition sources (open flame, spark, etc.,)
Incompatible materials	 : (lead): Oxidizing agent. (lead dioxide): Flammable materials, reducing materials. (lead sulfate): Strong oxidizing agents. (dilute sulfuric acid): Combustible materials, reducing materials, strong oxidizing agents, strong bases.
Hazardous decomposition products	: In case, there is a possibility that irritative or toxic gases or fumes (sulfur trioxide, carbon monoxide, mist sulfate, sulfur dioxide, hydrogen sulfide) are generated.

11. Toxicological Information

Indicate the information for each of components of lead acid battery as below.

\bigcirc Lead (electrode plate, terminal)	
Acute toxicity (Oral)	: No data.
Acute toxicity (Dermal)	: No data.
Acute toxicity (Inhalation: Gases)	: Classification not applicable because it is a solid in the definition of GHS.
Acute toxicity (Inhalation: Vapours)	: No data.
Acute toxicity	: No data.
(Inhalation: Dust and Mists)	
Skin corrosion/irritation	: No data.
Serious eye damage/eye irritation	: No data.
Respiratory or skin sensitization	: No data.
Germ cell mutagenicity	: Although there are contradicting results about the chromosome aberration in the peripheral blood lymphocytes from people who are engaged in lead-related work (IARC suppl.7 (1987), EHC 3 (1977), DFGOTvol.17 (2002), ACGIH (7th, 2001)), there are descriptions of lead itself having chromosome aberration/micronucleus inductive actions. Therefore, it was classified as Category 2.
Carcinogenicity	: From the below classifications, it was classified as Category 2.
	 IARC Supplement 7 (1987) and Japan Society for Occupational Health: 2B ACGIH (7th, 2001): A3 EPA (IRIS (1993)): B2
Reproductive toxicity	: Since there is the description that there is the affect for sperm formation disorder in human exposure example (EHC

No.PIS18-0009B Product name: Vent type lead-acid battery(paste type) Company name: GS Yuasa International Ltd. Page 8 / 19 Date of issuing: 2018/2/7 Date of revision: 2020/4/20 Latest confirmation date: 2020/4/20

3 (1977), ACGIH (7th, 2001), DFGOTvol.17 (2002)), and ovulation dysfunction was observed in the female occupation exposure example (EHC 3 (1977)), it was classified as "Category 1A". There are the descriptions about the relationship with neonatal developmental disorder of cognitive function (ACGIH (7th, 2001), DFGOTvol.17 (2002), PATTY (4th, 1994) and IARC 23 (1980)), and the descriptions about the relationship with the increase of miscarriage (DFGOTvol.17 (2002), and PATTY (4th, 1994)). However, the distinct conclusion has not obtained.

Specific target organ toxicity
(single exposure): Although there was a case report that renal dysfunction was
observed in the acute toxicity in human (DFGOT, vol.17
(2002)), there was the description that no kidney damage in
the subsequent epidemiologic study in the same source of
reference. Therefore, the data is insufficient for considering
the kidney as target organ, therefore, it is classified as
"classification not possible".

Specific target organ toxicity : Due to the descriptions that the target organs were (repeated exposure) hematopoietic system, nervous system, kidney, and cardiovascular system in DFGOTvol.17 (2002), that heme synthesis inhibitors, nephropathy and brain diseases were observed in the human exposure examples in EHC 3 (1977), ACGIH (7th, 2001), PATTY (4th, 1994), and IARC 23 (1980), that it affects to the peripheral nerve and function of central nerve system in humans exposure examples in EHC 3 (1977), ACGIH (7th, 2001), PATTY (4th, 1994), that it affects to cardiovascular system, such as high blood pressure in human exposure examples in EHC 3 (1977), ACGIH (7th, 2001), that the immunosuppressive effect was observed in human exposure examples in PATTY (4th, 1994), it is considered that the target organs were hematopoietic system, the kidney, central nervous systems, peripheral nervous system, cardiovascular system and immune system, and they all were classified as "Category 1". Although there are the descriptions of the case reports of thyroid or adrenal hypofunctions in EHC 3 (1977), each case reports are before 1970, and there is no similar report after that, since there is the description that no effects was observed in the thyroid in DFGOTvol.17 (2002), the thyroid and the adrenal gland were not considered as for target organs. Aspiration hazard : No data. Others : No information.

No.PIS18-0009B Product name: Vent type lead-acid battery(paste type) Company name: GS Yuasa International Ltd. Page 9 / 19 Date of issuing: 2018/2/7 Date of revision: 2020/4/20 Latest confirmation date: 2020/4/20

OLead dioxide (electrode plate)	
Acute toxicity (Oral)	: No data.
Acute toxicity (Dermal)	: No data.
Acute toxicity (Inhalation: Gases)	: Classification not applicable because it is a solid in the
	definition of GHS.
Acute toxicity (Inhalation: Vapours)	: No data.
Acute toxicity	: No data.
(Inhalation: Dust and Mists)	
Skin corrosion/irritation	: Since there is the description of "Probably a severe eye,
	skin, and mucous membrane irritant "(HSDB (2006)), it is
	considered that indicate severe irritation to skin. Therefore,
	it was classified as Category 2.
Serious eye damage/eye irritation	: Since there is the description of "Probably a severe eye,
	skin, and mucous membrane irritant "(HSDB (2006)), it is
	considered that indicate severe irritation to eyes. Therefore,
	it is classified as Category 2A.
Respiratory or skin sensitization	: No data.
Germ cell mutagenicity	: From the description of NTP DB (Access on February
	2006);
	Heritable germ cell mutagenicity tests: None.
	 Germ cell/ somatic cells in vivo mutagenicity tests:
	None.
	Germ cell/ somatic cells in vivo genetic toxicity test:
	None.
	 Positive (strong) results of multiple indicators in in
	vitro mutagenicity test: None.
	It was classified as "Classification not possible".
Carcinogenicity	: From the below classifications, it was classified as Category 2.
	• NTP (2005): R
	• IARC (1987): Group 2B
	• ACGIH (2001): A3
	 The Japan Society for Occupational Health : 2B
Reproductive toxicity	: Since lead is known as neurotoxic substance and
	reproductive toxic substance for human, it is classified as
	"Category 1A" based on experts' judgement.
Specific target organ toxicity	: For this substance, it is assumed that the classification
(single exposure, repeated	based on the effects of inorganic lead compounds.
exposure)	As the toxicity of inorganic lead compounds for humans,
	there is the description below;
	"acute effects and chronic effects of inorganic lead has been
	recognized almost the same symptoms. By inhalation or
	ingestion of inorganic lead, it has been reported that cause
	the convergence of the mouth, thirst. And also nausea,
	vomiting, upper abdominal discomfort, loss of appetite,

No.PIS18-0009B Product name: Vent type lead-acid battery(paste type) Company name: GS Yuasa International Ltd. Page 10 / 19 Date of issuing: 2018/2/7 Date of revision: 2020/4/20 Latest confirmation date: 2020/4/20

abdominal pain, constipation and the like has been reported as effects on the digestive organs.

Effects on hematopoiesis are typical effects of inorganic lead, it has been observed hemoglobin synthesis inhibition and anemia due to shortened of red blood cell life, caused by inhibition of δ -aminolevulinic acid and heme synthesis enzyme. Interstitial nephropathy as the effect to the kidneys, in addition to decreasing amount of urine, proteinuria, hematuria, urine cylinder, the proximal tubule disorder exhibiting a Fanconi syndrome typified by diabetes and amino acid urine is reported. Inorganic lead affects on the peripheral nervous system, in particular, muscle weakness in limbs, pain and convulsions are observed. In addition, although it is very rare case in adults, in case of being exposed to extremely high concentrations (details unknown), the effects on the central nervous system are observed such as ataxia, headache, paresthesia, depression and coma.

However, in effects on the central nervous system, particularly sensitive in children, and the symptoms with no restless, aggressive personality, difficulty concentrating, decline of memory and the like have become a problem in the U.S." (CERI Hazard Assessment Report 2001-9(2002))

Therefore, blood system, kidney and nervous system are considered to be target organs. From the above, it was classified as "Category 1(blood system, kidney, nervous system)".

Aspiration hazard Others

Lead sulfate (electrode plates)
 Acute toxicity (Oral)
 Acute toxicity (Dermal)
 Acute toxicity (Inhalation: Gases)

Acute toxicity (Inhalation: Vapours)

Acute toxicity (Inhalation: Dust and Mists) Skin corrosion/irritation

: No data.

: No information.

- : No data.
- : No data.
- : Classification not applicable because it is a solid in the definition of GHS.
- : No data.
- : No data.
- : No data. As effects on humans, although there is no data that can be obtained for local effects on the skin and mucous membranes by lead and inorganic lead compounds, there is the description of that there is likely to cause severe irritation and burns to the skin.

No.PIS18-0009B Product name: Vent type lead-acid battery(paste type) Company name: GS Yuasa International Ltd. Page 11 / 19 Date of issuing: 2018/2/7 Date of revision: 2020/4/20 Latest confirmation date: 2020/4/20 Serious eye damage/eye irritation : No data. As effects on humans, although there is no data indicating the local effects on the mucous membranes by lead and inorganic lead compounds, there is the description of that there is likely to cause severe irritation and burns to the eye. : No data. Respiratory or skin sensitization Germ cell mutagenicity : It is "Classification not possible" due to insufficient data of in vivo test. In addition, in the in vitro test, there is the negative report in Ames test. Moreover, although it may not be necessarily matched results have been obtained, there is also the positive result in chromosome analysis using peripheral blood of workers who received the occupational exposure of lead. However, the used method is insufficient in most of the tests, overall it stated that it cannot be conclusive evaluation of genotoxicity in human. Inorganic lead compounds in MAK / BAT (2010) are classified as germ cell mutagenicity 3A. : In carcinogenicity evaluation of IARC, it is classified as Carcinogenicity Group 2A as inorganic compounds. Therefore, this substance was classified as Category 1B. In addition, it is classified as 2B as a lead compound in The Japan Society for Occupational Health, and A3 as inorganic lead compound in ACGIH. Reproductive toxicity : Although there is no data of this substance, as effect on humans of inorganic lead compounds, an increase in the spontaneous abortion of pregnancy before 20 weeks was observed by a high concentration exposure of mothers in cases or epidemiological studies. There is description that exposure during the pregnancy is related increased in teratogenicity, low weight newborns and suppression of body weight gain after birth. Although decrease in sperm count and semen volume, morphological changes of sperm, and decreasing of sperm motility were observed by the occupational exposure, in most studies, it is observed dose-response relationship between these effects and exposure concentration of lead. and toxicity for sperm has been reported to have been unclear. Specific target organ toxicity : Although there is no data of this substance, neurotoxic effect of lead is known, and receives the influence of the (single exposure) lead in both the peripheral nerves and the central nervous system. Lead encephalopathy is one of the early symptoms of acute exposure. From also that there is a report of the suppression of the pituitary hands and nerve conduction velocity by the occupational exposure, it is classified as

No.PIS18-0009B Product name: Vent type lead-acid battery(paste type) Company name: GS Yuasa International Ltd. Page 12 / 19 Date of issuing: 2018/2/7 Date of revision: 2020/4/20 Latest confirmation date: 2020/4/20

"Category 1 (nervous system)". In high concentration acute exposure of lead and inorganic lead compounds, it causes dysfunction of the proximal tubule. There is the description that it causes Fanconi syndrome (diabetes, amino acid urine disease, phosphate urine disease and the like) as renal symptoms of acute lead poisoning. Therefore, it was classified as "Category 1 (kidney)".

Moreover, lead is also known to give a change in the blood system. There is the description that the hemoglobin synthesis inhibition and small blood cell anemia and hypochromic anemia due to shortened of red blood cell life are caused by δ -aminolevulinic acid and heme synthesis enzyme are inhibited. Therefore, it is classified as "Category 1 (blood system)".

Other, colic is the initial symptoms of occupational exposure or high concentration acute exposure. Since there is the description of the associated symptoms such as constipation, severe abdominal pain, nausea, vomiting, loss of appetite, it is classified as "Category 1 (digestive system)".

: Although there is no data of the substance, there is the (repeated exposure) description that in high concentration repeated exposure by lead and inorganic lead compounds, it leads to irreversible changes to kidney including tubular atrophy, interstitial fibrosis glomerular sclerosis, and eventually it cause chronic nephritis. Therefore, it was classified as "Category 1(kidney)".

> In addition, there is the report of the lead epidemiological study, hemoglobin concentration and hematocrit value of poisoning patients were significantly decreased compared with control subjects of non-exposure.

There is the description that the hemoglobin synthesis inhibition and small blood cell anemia and hypochromic anemia due to shortened of red blood cell life are caused by δ -aminolevulinic acid and heme synthesis enzyme are inhibited. Therefore, it was classified as "Category 1 (blood system)".

On the other hand, there is the research study to support the relationship between the chronic lead poisoning and myocardial injury, and there is reported that abnormal electrocardiogram in workers of lead poisoning was observed. In addition, from the data of epidemiological studies, since it has been concluded that internal absorption of lead causes a significant increase in blood pressure in both diastolic and systolic of the heart, it was classified as

Specific target organ toxicity

Category 1(cardiovascular).

Aspiration hazard Others	Moreover, suppression of motor nerve conduction velocity was observed in worker who blood concentration of lead is high, and also there is a report of the Parkinson's syndrome has been observed in seven out of nine that have been exposed for more than 30 years in a lead-acid battery. Therefore, it was classified as "Category 1(nervous system)". : No data. : No information.
\bigcirc Dilute sulfuric acid (electrolyte)	
Acute toxicity (Oral)	: Based on the Rat LD ₅₀ value: 2140mg/kg and the description of the death case report by the oral ingestion in humans (amount of intake is unknown), it was classified as Category 5 ("Not classified" by JIS classification).
Acute toxicity (Dermal)	: No data.
Acute toxicity (Inhalation: Gases)	: Classification not applicable because it is a liquid in the definition of GHS.
Acute toxicity (Inhalation: Vapours)	: No data.
Acute toxicity	: Based on rat LC $_{50}$ value: 0.375mg/L (4 hour exposure) and
(Inhalation: Dust and Mists)	347ppm (1-hour exposure) (4 hour equivalent value: 0.347mg/L), it was classified as Category 2.
Skin corrosion/irritation	: Since pH of concentrated sulfuric acid was 1 or less, it was judged to be corrosive substance in accordance with the GHS classification standards, and classified as Category 1A-1C.
Serious eye damage/eye irritation	: There is the description that the critical damage to the eye accompanied by lysis of anterior chamber of eye was observed in accident case of human. And also from the description that the moderate irritation with 5% solution and the severe irritation with 10% solution were observed to the eye of rabbit, therefore, it was classified as "Category 1".
Respiratory or skin sensitization	 Respiratory sensitization: No data. Skin sensitization: There is no test data on skin sensitizing of sulfuric acids. Although sulfuric acid has been industrially used for several decades, there is no case report of skin sensitization while skin injuries by skin irritation are well known. Although an extensive amount of sulfate ion exists internally (the sulfate ion in serum ~33 mmol/L, and 50 times more in cells), allergic reactions do not occur. In allergic test of sulfuric acid salt of metal, even if allergic positive with metal may occur, sulfuric ion is presumed to

No.PIS18-0009B Product name: Vent type lead-acid battery(paste type) Company name: GS Yuasa International Ltd. Page 14 / 19 Date of issuing: 2018/2/7 Date of revision: 2020/4/20 Latest confirmation date: 2020/4/20

result in allergic negative as is suggested by the negative results in sulfate of zinc. Based on the description that conclusion is obtained from the results mentioned above that sulfate does not cause allergy to human, it is classified as "Not classified".

Germ cell mutagenicity : For in vivo, there is not any test data which the reproductive cells and the somatic cells were used. For in vitro mutagenicity tests, there is the positive result only in the test system with the single indicator (chromosomal aberration test). However, there are negative results in other indices. Therefore, it was classified as "Classification not possible".

Carcinogenicity : Occupational exposure of the mist of the inorganic strong acid including sulfuric acids is classified as group 1 according to IARC, as A2 according to ACGIH, and as K according to NTP.

Respect the evaluation of IARC and the latest NTP, it was classified as category 1. However, sulfuric acids itself was classified as the category 4 according to DFGOT. And, since none of those institutions have carried out the carcinogenic classification, it was classified as "Classification not possible".

Reproductive toxicity : In inhalation exposure test using rabbit and mouse in fetal organogenesis period, it is not observed of fetotoxicity and teratogenicity at the dose causing no maternal toxicity in both species. And also, the effect on the reproductive organ of both sexes is not observed in chronic toxicity test and carcinogenicity test. Since the direct effect by irritation/corrosive is the main toxicity, it is judged that there is no concern that indicates the reproductive toxicity, therefore, it was classified as "Not classified".

Specific target organ toxicity
(single exposure): There is the descriptions that in the inhalation exposure of
low concentration in humans, airway irritation symptoms
such as cough and breath shortness are observed and at
high concentration exposure, addition to acute effects such
as cough, breath shortness and hemoptysis shedding etc.,
permanent effects such as functional depression of lungs,
fibrosis and emphysema are observed. Additionally, there is
the description that hemorrhage and dysfunction in lungs
were observed in 8-hour inhalation exposure using guinea
pigs. Based on these descriptions, it was classified as
"Category 1 (respiratory systems)".

Specific target organ toxicity
(repeated exposure): In the 28-day inhalation exposure test using rat, cell
proliferation in laryngeal mucosa is observed in guidance
value range of Category 1. In the 14 to 139-day repeated
inhalation exposure test using the guinea pigs, respiratory

No.PIS18-0009B Product name: Vent type lead-acid battery(paste type) Company name: GS Yuasa International Ltd. Page 15 / 19 Date of issuing: 2018/2/7 Date of revision: 2020/4/20 Latest confirmation date: 2020/4/20

and lung disorder, such as nasal-septum dropsy, pulmonary emphysema, atelectasis, hyperemia, dropsy, bleeding and thrombosis of bronchioles are observed at the concentration range of guidance value of Category 1. Furthermore, in the 78-week inhalation exposure test using a cynomolgus, histological change as hyperplasia of a cell, the wall thickening, etc. in bronchioles of lungs were observed at the dosage (0.048 mg/L, 23.5 Hr/Day) of the guidance value range of Category 1. From the above, it was classified as Category 1 (respiratory systems).

Aspiration hazard: No data.Others: No information.

12. Ecological Information

Indicate the information for each of components of lead acid battery as below.

\bigcirc Lead (electrode plate, terminal)	
Ecotoxicity	: No data.
Persistence/degradability	: No data.
Bioaccumulation	: No data.
Mobility in soil	: No information.
Hazardous to the ozone layer	: Not contain ingredients listed in the Annex of the Montreal
	Protocol.
OLead dioxide (electrode plate)	
Ecotoxicity	: No data.
Persistence/degradability	: No data.
Bioaccumulation	: No data.
Mobility in soil	: No information.
Hazardous to the ozone layer	: Not contain ingredients listed in the Annex of the Montreal Protocol.
⊖Lead sulfate	
Ecotoxicity	: Crustacean: Daphnia magna, 48hr-IC₅₀ = 0.5mg/L
	(Acute hazardous to the aquatic environment : Category 1)
	Reliable chronic toxicity data has not been obtained. Since it
	is metal compound, the behavior in water is not known.
	Because acute toxicity is category 1, chronic hazardous to
	the aquatic environment was classified as "Category 1".
Persistence/degradability	: No data.
Bioaccumulation	: No data.
Mobility in soil	: No information.
Hazardous to the ozone layer	: Not contain ingredients listed in the Annex of the Montreal Protocol.

\bigcirc Dilute sulfuric acid (electrolyte)	
Ecotoxicity	: Fishes: Bluegill, 96hr-LC₅₀ = 16-28mg/L
	(Acute hazardous to the aquatic environment : Category 3)
	Toxicity factor is considered to be aqueous solution which
	becomes strong acid, but toxic effect is eased by the buffer
	action in the environmental water. Therefore, Chronic
	hazardous to the aquatic environment was classified as "Not
	classified".
Persistence/degradability	: No data.
Bioaccumulation	: No data.
Mobility in soil	: No data.
Hazardous to the ozone layer	: Not contain ingredients listed in the Annex of the Montreal
	Protocol.

3. Precautions for Disposal	
Disposal considerations	: In the disposal, follow "Waste Management and Public
	Cleansing Law" and the standards of the local government.
	Entrust disposal to industrial waste disposal contractor who
	have obtained a license from local governor, otherwise if the
	local government is performing waste disposal, entrust then
	disposal.

14. Transport Information

-	
International regulations(dangerous goo	ds)
Inland transport	: Follow the regulation under ADR/RID.
Sea transport	: Follow the regulation under IMO.
Air transport	: Follow the regulation under ICAO/IATA.
UN number	: 2794
UN class	: Corrosive substance/Class 8
Proper shipping name	: BATTERIES, WET, FILLED WITH ACID, electric storage
Packing group	:-
Special requirements	: IMO SP295
	IATA A51, A164, A183, A802
Marine pollutant	: Not applicable
Japan domestic regulations	
Inland transport	: Follow the regulation of Fire Service Act and Poisonous and
	Deleterious Substances Control Law.
Sea transport	: Follow the regulation of Ship Safety Law.
Air transport	: Follow the regulation of Civil Aeronautics Act.
Special safety measures and condition	: Avoid mixed load with other substances as much as
for transport	possible.
	Handle the dilute sulfuric acid so as not to leak by
	overturning or falling.
	5 5

	No.PIS18-0009B
	Product name: Vent type lead-acid battery(paste type)
	Company name: GS Yuasa International Ltd.
	Page 17 / 19
	Date of issuing: 2018/2/7
	Date of revision: 2020/4/20
	Latest confirmation date: 2020/4/20
	Load to not overturning, falling and damage, and take
	prevention of cargo collapse securely.
	Avoid transport under the direct sunlight and high
	temperature.
	Transport in accordance with the standards of other related
	laws and regulations.
Emergency response guid	deline : 154
number(North America)	
HS code	: 8507.20 (Lead-acid batteries(except for starting piston
	engines))
Country of origin	: JAPAN
Country of origin	

15. Regulatory Information

There are not laws and regulations applicable for the lead-acid battery itself. Describe the information about the components below.

Industrial Safety and Health Act	 Dangerous and Harmful Substances Subject to Indicate Their Names (Article 57 of the Act) Lead components: lead dioxide, lead sulfate Dangerous and Harmful Substances Subject to Notify Their Names (Article 57-2 of the Act) Lead and its inorganic compounds : lead, lead dioxide, lead sulfate Sulfuric acid: dilute sulfuric acid. Corrosive liquids (Article 326 of the regulation) Sulfuric acid: dilute sulfuric acid Specified Chemical Substances (Article 2 of The Ordinance on Prevention of Dangers Due to Specified Chemical Substances, paragraph 1) Category 3 substance Sulfuric acid: dilute sulfuric acid Lead (Appended Table 4 of the Enforcement Ordinance No.1 of Article 1 of the Ordinance on Prevention of Lead Poisoning.) Lead Lead compounds (Appended Table 4 of the Enforcement Ordinance No. 4 of Article 1 of the Ordinance on Prevention of Lead Poisoning.) Lead dioxide, Lead sulfate
Labor Standards Act	 Illness chemical substances (Article 75 of the Act, paragraph 2, article 35 of the Enforcement Regulations, Appended table of 1-2, no.4) Lead and its compounds Lead, lead dioxide, lead sulfate

	No.PIS18-0009B Product name: Vent type lead-acid battery(paste type) Company name: GS Yuasa International Ltd. Page 18 / 19 Date of issuing: 2018/2/7 Date of revision: 2020/4/20 Latest confirmation date: 2020/4/20
Poisonous and Deleterious Substances Control Act	: Deleterious Substances (Article 2 of the designated ordinance)
	- Lead compounds: lead dioxide
Act on Confirmation, etc. of Release	- Sulfuric acid: dilute sulfuric acid : Class I Designated Chemical Substances (Paragraph 2 of
Amounts of Specific Chemical	Article 2 of the Act, Appended Table 1 of Article 1 of the
Substances in the Environment and	Enforcement Ordinance)
Promotion of Improvements to the	- Lead
Management Thereof	Specified Class I Designated Chemical Substances
	(Paragraph 2 of Article 2 of the Act, Article 4 of the
	Enforcement Ordinance)
	- Lead compounds: lead dioxide, lead sulfate
Fire Service Act	: Hazardous material Category 1 Oxidizing solid
	- Chromium, lead or oxide of iodine
	- Lead dioxide
	: Substances Inhibiting Fire Fighting
	- Lead dioxide
	- Sulfuric acid: dilute sulfuric acid
Marine Pollution Prevention Law	: Noxious liquid substances
	- Category Y: Dilute sulfuric acid
Civil Aeronautics Act	: Article 194 of Enforcement Regulations, Appended Table 1
	of the Notification for Establishing Standards for the
	Carriage of Dangerous Goods in Ships
	- Oxidizing substances: lead dioxide
	- Corrosive substance: lead sulfate (which the content of
	free acid is more than 3 wt%)
	- Corrosive substance: dilute sulfuric acid
Ship Safety Act	: Article 2,3 of the Dangerous Goods Regulations, Appended
	Table 1 of the Notification for Establishing Standards for the
	Carriage of Dangerous Goods in Ships
	- Oxidizing substances: lead dioxide
	 Corrosive substance: lead sulfate (which the content of free acid is more than 3 wt%)
	- Corrosive substances: dilute sulfuric acid
Water Pollution Prevention Act	: Noxious Substances (No.1 of Paragraph 2 of Article 2 of the
	Act)
	- Lead and its compounds:
	Lead, lead dioxide, lead sulfate
	: Designated Substances (Paragraph 4 of Article 2 of the Act)
	Sulfuric acid: dilute sulfuric acid
Act on Port Regulations	- Oxidizing Substances: lead dioxide
5	- Corrosive Substance: lead sulfate (which the content of
	free acid is more than 3 wt%)
	- Corrosive Substances: dilute sulfuric acid

16. RoHS Instruction

Lead and lead compound contained in the lead-acid battery are off the subject of the RoHS instruction.

17. Other Information

Electrochemical reaction formula:								
Positive	Electrolyte	Negative		Positive		Electrolyte	Э	Negative
PbO ₂ +	$2H_2SO_4 \hspace{0.1in} + \hspace{0.1in}$	Pb	Charge<>Discharge	PbSO ₄	+	$2H_2O$	+	PbSO ₄
Lead Dioxide	Sulfuric Acid	Lead		Lead sulfate		Water	L	ead sulfate

(Land transportation In U.S.A and Canada)

According to law by Department of Transportation(DOT), "Batteries, wet, filled with acid "must be described on battery or package in order to call the attention of nature of transport goods to the drivers.

(TSCA)

Ingredients in GS Yuasa batteries are listed in the TSCA registry as follows:

Components		CAS number	TSCA status		
Electrolyte	Sulfuric Acid (H ₂ SO ₄)	7664-93-9	listed		
	lead (Pb)	7439-92-1	listed		
Inorganic lead compound	Lead dioxide (PbO ₂)	1309-60-0	listed		
	Lead sulfate (PbSO ₄)	7446-14-2	listed		
	Calcium (Ca)	7440-70-2	listed		
	Tin (Sn)	7440-31-5	listed		
	Barium (Ba)	7440-39-3	listed		

(California Proposition 65)

Battery posts, terminals and related accessories contain lead and lead compounds, and other chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. Wash hands after handling.

Reference:

Globally Harmonized System of classification and labelling of chemicals, (5th ed., 2013), UN JIS Z 7253:2012

- 1) NITE GHS classification data.
- 2) ECHA Home page (http://echa.europa.eu/information-on-chemicals)
- 3) NITE CHRIP (http://www.safe.nite.go.jp/japan/sougou/view/SystemTop_jp.faces)

Notice:

The contents described in this sheet are prepared based on the data and information currently available to us. However, it does not intend to be any guarantees in regard to content, physical and chemical properties, hazards, etc.

Please handle this product in the responsibility of the user after referring to this sheet.

In addition, the precautions are intended for normal handling. Please use under implementing safety measures that are suitable for application/usage if you want to special handling.